



Specialized Camber Comp

Specifications

FRAME	M4 hydroformed tubing, sealed cartridge bearing pivots, disc only, Command Post routing, replaceable derailleur hanger, bolt on cable guides, 120mm travel
FORK	RockShox Recon Silver TK, Turn Key damper, Solo Air, alloy steerer, rebound adj., disc only, 120mm travel
REAR SHOCK	RockShox Ario RL, air spring, rebound adj. and LO, 7.875x2.0"
HEADSET	Semi-Integrated 1-1/8" Aheadset--Steel Cups, Caged Bearing, with Alloy Laser Top Cap, Custom Curved 1 x 15mm + 2 x 5mm Straight Washers
STEM	1 1/8" upper and lower campy style cartridge bearings for integrated alloy HT
HANDLEBAR	Specialized XC low-rise, 6061 butted alloy, 680mm wide, 8 degree back sweep, 6 degree up, 31.8mm
GRIPS	Specialized lock-on, S/M: Grappler, Other: Rocca
SHIFTERS	Shimano SL-M430 Alivio, 9-speed, trigger
FRONT DERAILLEUR	Shimano FD-M660 SLX, E-type for DMD, top swing, bottom pull
REAR DERAILLEUR	Shimano RD-M662 SLX Shadow, long cage
CRANKSET	Shimano FC-M430, Octalink spline, replaceable rings, S: 170mm, others: 175mm
BOTTOM BRACKET	Shimano BB-ES25, Octalink spline, cartridge bearing
CHAIN	KMC X9, 9-speed, w/ reuseable Missing Link
FREEWHEEL/CASSETTE	Shimano HG30, 9-speed, 11-34t
BRAKE LEVERS	Tektro Draco hydraulic
FRONT BRAKES	Tektro Draco, hydraulic disc, ceramic pad, Light Wave rotor, S/M:180mm rotor, L/XL:203mm
REAR BRAKES	Tektro Draco, hydraulic disc, ceramic pad, Light Wave rotor, S/M:160mm rotor, L/XL:180mm
SADDLE	Specialized BG Rival, 143mm width
SEAT POST	6061 alloy, 2-bolt micro adjust, setback head, 30.9mm, S/M:350mm, others:400mm
FRONT HUB	Specialized Hi Lo disc, QR, 28h
REAR HUB	Specialized Hi Lo disc, double sealed cartridge bearing, QR, 32h
RIMS/WHEELSET	Custom DT Swiss 445D, disc, double wall, pin joint, eyelets, 24mm, 28/32h
TYRES	Specialized „The Captain“ Sport, 60 TPI, wire bead, 26x2.0"
SPOKES	1.8mm (15g) stainless
PEDALS	Alloy platform, 9/16"
FRAME SIZE	S, M, L, XL

HIMAL Spezialreisen
M. Hoeschele
Rißegger Steige 53
D-88400 Biberach

G-P-O, Post-Box 4649
Kathmandu, Nepal

T. 07351 300936
F. 07351 300935

info@himal.de
www.himal.de

Bankverbindung
Kreissparkasse Biberach
BLZ 654 500 70
Konto-Nr. 7 073 528



Felt Compulsion 2

Specifications	
FRAME	Felt Equilink „ALL DAY“ Full Suspension, 7005 Double-Butted Aluminum w/Hydroform TT & NEW ALLOY SEAT AND CHAINSTAYS 145mm travel, 45mm Integrated Head Tube, Replacable Derailleur Hanger
FORK	RockShox Pike 409 95-140mm, U-Turn Coil fork, External rebound, Internal low speed compression to ‚Lock‘ with external Floodgate Magnesium lowers, includes Maxle 360 20mm, IS disc mount. Crown: Forged, 6061 T-6 aluminum, Max rotor: 210mm. Steerer tube: 4130 steel 1 1/8
REAR SHOCK	FOX Float Air 7.875 x 2.0, 12mm Shaft Diameter, 29mm Body Diameter, Aluminum, External Rebound Adjust, 315 Grams
HEADSET	Fully-Integrated Aheadset Threadless Type, Cane Creek Compatible (45 Degree), 1-1/8“, Sealed Cartridge Bearing, 28.6/41/30mm Diameter, 10.2mm Stack Height, without Top Cap, 73 Grams
STEM	New Felt All Mountain Stem 3D Forged Aluminum 4 bolt Split Clamp design. 7 degree rise, CP chromo hardware 290grams 31.8 Bar Bore. Extensions S-M=80mm L=90mm XL=100mm Sand Blast Black Anodized
HANDLEBAR	NEW Felt MTB XC/AM RISER BAR 1/2“ Rise double butted 6061DB, 31.8mm bar bore, Width 680mm, with NEW 2009 FELT LASER LOGO'S
GRIPS	Felt All Mountain Grip Custom „LOCK-ON“ Design with Alloy Ends Single-Density Extra-Soft & Sticky (Recipe #25) Durometer, 130mm Length, 30mm OD With 2 2008 Felt lazer Logo
SHIFTERS	SRAM X-7, 1-1 Trigger 9 speed Shifter 9 speed right 3 speed (Shimano compatible) Left 262g
FRONT DERAILLEUR	Deore XT, FD-M770-E E-Type Down-Swing Dual-Pull Band-Type, 34.9mm Seat Tube, Dual Pull, 66-69 Degree CS Angle
REAR DERAILLEUR	2008 X-9, long cage, ‚Aluminum alloy links and forged B-knuckle, High Strength Grilon P-knuckle, sealed cartridge bearing upper pulley
CRANKSET	Truvativ Firex SX 2-Piece Crank, Forged Aluminum Arms, 9-Speed, 44/32/22T 7075 Alloy outer Ring, Steel middle and inner ring, Giga X-Pipe XR BB
CHAIN	Super-Narrow for 9-Speed
FREEWHEEL/CASSETTE	Sram PG-950 Cassette Sprocket, 9-Speed, 11, 12, 14, 16, 18, 21, 24, 28, 34 Tooth,
BRAKE LEVERS	Included w/Brakes
BRAKES	AVID Juicy 3 Hydraulic IS Mount, 2-Finger Levers
FRONT HUB	New Shimano HB-RM65 w/CenterLock, 32H, with Quick Release
REAR HUB	Shimano FH-RM65 8/9 Speed Cassette w/CenterLock, 32H, with Quick Release
RIMS/WHEELSET	WTB SX 24 Disc Doublewall, 26 x 1.5 x 32H, 24mm Width, Schraeder Valve, Black Anodised, 460g
SPOKES	Sandblast Black Stainless 15G, Brass Nipples
PEDALS	MTB Design Steel Cage / PP Body
FRAME SIZE	15,5“, 17,5“, 19,5“, 21,5“

HIMAL Spezialreisen
 M. Hoeschele
 Ribegger Steige 53
 D-88400 Biberach
 G-P-O, Post-Box 4649
 Kathmandu, Nepal
 T. 07351 300936
 F. 07351 300935

info@himal.de
 www.himal.de

Bankverbindung
 Kreissparkasse Biberach
 BLZ 654 500 70
 Konto-Nr. 7 073 528



Felt Q620	
Specifications	
FRAME	Felt 6061 Butted Aluminum, Fully Hydroformed Down Tube, Oversized Semi-Integrated
FORK	SR Suntour XCM-HLO With Hydraulic lockout 100mm travel, Pre-load, Internal spring, Alloy Crown, Alloy lower with STKM Stanchions. With spring seal design, Disc Specific Lowers
HEADSET	Semi-Integrated 1-1/8" Aheadset--Steel Cups, Caged Bearing, with Alloy Laser Top Cap, Custom Curved 1 x 15mm + 2 x 5mm Straight Washers
STEM	FELT One-Piece Melt-Forged Design, 1-1/8" Threadless Aluminum, 4-Bolt, 15 Degree Rise. CP Hardware BLAST BLACK Extensions: 13.5/15.5/17.5=90mm; 19.5/21.5=110mm
HANDLEBAR	Aluminium Riser, 35mm Rise, 25.4 Bar Bore, 8 degree Bend, 4 Degree up sweep, with Felt Laser Logos. Widths: 13.5/15.5/17.5=600mm; 19.5/21.5=640mm
GRIPS	Felt Dual-Density Extra-Soft & Sticky (Recipe #25)center with Hard Outer Durometer, 130mm Length, 30mm OD, Grey outer/Blk grip section
SHIFTERS	Shimano Alivio SL-M410, 24 Speed RAPIDFIRE Shifters
FRONT DERAILLEUR	Shimano ALIVIO FD-M410 Dual Pull
REAR DERAILLEUR	Shimano Deore „Shadow“ Top-Normal Version RD-M592
CRANKSET	Shimano FC-M361-L Crankset with Interchangeable rings 3 Piece crank Melt-Forged
BOTTOM BRACKET	TH Cartridge Type, Cr-Mo Axle & Cup
CHAIN	KMC Z7 (8-Speed) Silver Outer
FREEWHEEL/CASSETTE	SRAM PG-830, 8-Speed Cassette, 11-32T
BRAKE LEVERS	Tektro Auriga Hydraulic
BRAKES	Tektro Auriga Hydraulic Disc Brakes Twin Piston design, Rotors: 180mm Front; 160mm Rear
SADDLE	Felt „RXC“ Comfort, Low Side Profile Look with Wide/Flat/Plush Top, Double-Density Base, Satin Steel Rails
SEAT POST	Felt Alloy Micro-Adjust, 100% Black, 6061 Low-Profile Forged Head & Extruded Rail Clamps, 30.9mm x 350mm (CEN)
FRONT HUB	Cold-Forged Aluminium Body, 32H, 6 Bolt disc compatible with Rubber Seals & Alloy Quick Release
REAR HUB	Shimano FH-M475, 6-Bolt Type Rotor Mount, 9 Speed Cassette 32H, with Quick Release
RIMS/WHEELSET	WTB SX 24 Disc Doublewall, with Single Eyelets, 26 x 1.5 x 32H, 24mm Width, Presta Valve, Black Anodized, 460g
TYRES	FELT THC XC Trail Highway City 26 x 2.1 30TPI Wire Bead, with Presta valve Inner Tubes
SPOKES	Stainless 14G, Brass Nipples
PEDALS	MTB Design Steel Cage / PP Body
FRAME SIZE	15,5", 17,5", 19,5", 21,5"

HIMAL Spezialreisen
M. Hoeschele
Rißegger Steige 53
D-88400 Biberach
G-P-O, Post-Box 4649
Kathmandu, Nepal
T. 07351 300936
F. 07351 300935
info@himal.de
www.himal.de

Bankverbindung
Kreissparkasse Biberach
BLZ 654 500 70
Konto-Nr. 7 073 528



Felt Q620

Specifications

FRAME	Felt Hydroform 6061 PG Aluminium, Hydroform Top Tube, Monostay Design, Oversized Semi-Integrated Head Tube, Replaceable Derailleur Hanger, Rack & Fender Mounts, Disc Brake Specific.
FORK	RST Gila TnL Lockout, Hi-Ten 1-1/8" Steer Tube, Forged + CNC 6061 Crown, Hi-Ten 28.6mm Ti-Colour Stanchion, 125mm Pitch, Leading Axle, One-Piece Aluminium Lower + Brace, Coil Spring + MCU, 80mm travel, with Super Low-Profile Mini Boots, and Preload Adjust, 2.1 Kg, Disc Brake Specific Lower Legs
HEADSET	Semi-Integrated 1-1/8" Aheadset--Steel Cups, Caged Bearing, with Alloy Laser Top Cap, Custom Curved 1 x 15mm + 2 x 5mm Straight Washers
STEM	One-Piece Melt-Forged Design, 1-1/8" Threadless Aluminium, 4-Bolt, 10 Degree Rise. Extensions: 13.5/15.5=80mm; 17.5/19.5=100mm; 21.5=120mm
HANDLEBAR	Butted Aluminium, 30mm Rise, 6 degree Bend, with Felt Laser Logos. Widths: 13.5-17.5=580mm; 19.5=600mm; 21.5=620mm
GRIPS	Felt Single-Density Extra-Soft & Sticky (Recipe #25) Durometer, 130mm Length, 30mm OD, with Felt Bubble-Tech Custom External End Plugs
SHIFTERS	New Shimano Alivio ST-M405, 24 Speed
FRONT DERAILEUR	2007 Shimano Alivio FD-M411 Top Pull
REAR DERAILEUR	Shimano Shimano Deore Top-Normal Version RD-M511
CRANKSET	truvativ X-Flow, Melt-Forged Aluminium, 42/34/24T Steel Rings, w/Chain-guard. Lengths: 13.5-15.5=170mm; 17.5-21.5=175mm
BOTTOM BRACKET	TH Cartridge Type, Cr-Mo Axle & Cup
CHAIN	Shimano HG-50 (8-Speed) Silver Outer
FREEWHEEL/CASSETTE	New Shimano HG-40, 8-Speed Cassette, 11-30T
BRAKE LEVERS	Shimano Alivio, Integrated w/Shifters
BRAKES	Shimano Alivio BRM-415 Mechanical, Rotors: 180mm Front & 160mm Rear
SADDLE	Felt "Facade" Comfort, Low Side Profile Look with Wide/Flat/Plush Top, Double-Density Base, Satin Steel Rails
SEAT POST	Alloy Micro-Adjust, 100% Black, Low-Profile Head & Extruded Rail Clamps, 27.2mm x 350mm
FRONT HUB	New Shimano HB-RM65 w/CenterLock, 32H, with Quick Release
REAR HUB	Shimano FH-RM65 8/9 Speed Cassette w/CenterLock, 32H, with Quick Release
RIMS/WHEELSET	WTB SX 24 Disc Doublewall, 26 x 1.5 x 32H, 24mm Width, Schraeder Valve, Black Anodised, 460g
TYRES	HFR Rocky Wolf 26 x 2.1, 100% Black
SPOKES	Sandblast Black Stainless 15G, Brass Nipples
PEDALS	MTB Design Steel Cage / PP Body
FRAME SIZE	15,5", 17,5", 19,5", 21,5"

HIMAL Spezialreisen
M. Hoeschele
Rißegger Steige 53
D-88400 Biberach

G-P-O, Post-Box 4649
Kathmandu, Nepal

T. 07351 300936
F. 07351 300935

info@himal.de
www.himal.de

Bankverbindung
Kreissparkasse Biberach
BLZ 654 500 70
Konto-Nr. 7 073 528